



# Conector Manguito



## CARACTERÍSTICAS TÉCNICAS

**Material:** Cobre electrolítico

**Acabado:** Estaño

Fabricados con cobre aleación T2/C11000.

Requisitos según UL486

**Garantía:** 6 meses

## CERTIFICACIONES



| Código | Referencia | Modelo   | Sección Cable | L (mm) | L 1 (mm) | D $\phi$ (mm) | Peso (Kg) | Embalaje (Unidad) |
|--------|------------|----------|---------------|--------|----------|---------------|-----------|-------------------|
| 103023 | 90032940   | GP10-UP  | 8 AWG         | 30     | 15,0     | 6,7           | 0,004     | 50                |
| 103024 | 90032930   | GP16-UP  | 6 AWG         | 35     | 17,5     | 7,4           | 0,005     | 50                |
| 103025 | 90032920   | GP25-UP  | 4 AWG         | 40     | 20,0     | 9,0           | 0,0054    | 50                |
| 103026 | 90032910   | GP35-UP  | 2 AWG         | 45     | 22,5     | 1,3           | 0,14      | 25                |
| 103027 | 90032950   | GP50-UP  | 1 AWG         | 50     | 25,0     | 12,5          | 0,15      | 10                |
|        |            |          | 1/0 AWG       |        |          |               |           |                   |
| 103028 | 90032960   | GP70-UP  | 2/0 AWG       | 55     | 27,5     | 14,5          | 0,02      | 10                |
| 103029 | 90032980   | GP95-UP  | 3/0 AWG       | 60     | 30,0     | 17,0          | 0,03      | 10                |
|        |            |          | 4/0 AWG       |        |          |               |           |                   |
| 103030 | 90035575   | GP150-UP | 250 MCM       | 70     | 35,0     | 21,0          | 0,07      | 3                 |

## MEDIDAS

